

Specifications

Items		Specification	
		IP-900E (Encoder)	IP-900IID (Decoder)
Video	Input / Output	1 x HD-SDI (SMPTE 292M)*1/ SD-SDI (SMPTE 259M), 1 x HDMI, 1 x NTSC/PAL	1 x HD-SDI (SMPTE 292M)/ SD-SDI (SMPTE 259M), 1 x HDMI, 1 x NTSC/PAL
	Coding	ITU-T H.264/MPEG-4 AVC (ISO/IEC 14496-10) HP@L4*1, MP@L4*1 ITU-T H.264/MPEG-4 AVC (ISO/IEC 14496-10) HP@L3, MP@L3	
	Resolution, Frequency, Bit Rate	1080i x 1920/1440/960 (50/59.94Hz) : 0.5 to 27 Mbps, 720p x 1280/960/640 (50/59.94Hz) : 0.5 to 27 Mbps 480i x 720/352 (59.94Hz), 576i x 720/352 (50Hz) : 150 Kbps ~ 10 Mbps 240i x 352 (59.94/29.97Hz), 288i x 352 (50/25Hz) : 25 to 384 Kbps*2	
Audio	Input / Output	2 x SDI embedded** (SMPTE 299M*1/272M), 1 x HDMI, 1x Unbalanced Analog Pair (RCA)	1 x SDI embedded (SMPTE 299M/272M), 1 x HDMI, 1x Unbalanced Analog Pair (RCA)
	Coding	MPEG-1 Layer2 (ISO/IEC 11172-3) : 2ch (2 x Stereo) 128,256,384 Kbps/Stereo MPEG-2 AAC (ISO/IEC 13818-7) : 2ch (2 x Stereo) 58,64,128,256,384 Kbps/Stereo	
Multiplexing Method		MPEG-2 TTS, MPEG-2 TS	
Ancillary Data		NIT (Carrier ID), SDT	
Transport		RTP/UDP/IP, UDP/IP	
Error Correction		Fujitsu FEC and ARQ, Pro-MPEG FEC	
Network	IPv4	PPPoE, DHCP, SNTP, SNMP v2c, IGMP v2	
	IPv6	SNTP, SNMP v2c, MLDv2	
Control		Web GUI, SNMP	
Additional Functions		Recoding*3, Dual encoder, Superimpose	----
Network Interface		1 x 10BASE-T/100BASE-TX	
Data (outside MUX.)		RS-232C (Pass-thru)	
External Dimensions (W x D x H)		210 x 300 x 42 mm	
Weight		Approx. 2 kg	
Power		AC100 ~ 240V	
Power Consumption		38VA	35VA
Temperature		-10 ~ 55 degrees C	
Humidity		20 ~ 90RH (No condensations)	
Compliance		UL, CE, FCC, RoHS, KC	

*1: IP-900E with HD option software, IP-900IID

*2: IP-900E only

*3: Need Optional CF card

*4: Selectable 2ch (2 x Stereo) mode (Single Encoder) or 1ch (1 x Stereo) mode (Dual Encoder).

Note) HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

Front Panel

IP-900E



IP-900IID



Rear Panel

IP-900E



IP-900IID



● The specifications are subject to change without notice.

NUBICOM
한국후지쯔 IP-Codec 총판

서울특별시 영등포구 경인로 775(문래동 3가, 에이스하이테크시티 3동 2층 201호)
TEL: 070-7872-0755 FAX: 02-2167-3801 E-mail: its@nubicom.co.kr

한국후지쯔 (주)
<http://www.fujitsu.com/kr/>

서울특별시 종로구 종로1 (교보생명 빌딩)

본 카탈로그에 기재되어있는 회사명 및 상품명은 일반적으로 각 사의 상표 및 등록상표입니다.

이 카탈로그 내용은 사전 예고 없이 변경될 수 있습니다. (2019.02)